

1W	Colour Temp (K)	4000	6000
	Luminous Flux @ 45° (lm)	100	100

PRODUCT CODE

LT-Ingr-2/ / /

- LED COLOUR**
- 30 3000K
- 50 5000K
- R Red
- G Green
- B Blue
- A Amber
- BEAM ANGLE**
- 12 12°
- 45 45°
- FINISH**
- ST 316 Stainless Steel

APPLICATIONS

Designed for use in areas such as pathways, lobbies, decking, ponds, and swimming pools - the LT-Ingr-2 luminaire is very versatile.


DESCRIPTION

The LT-Ingr-2 in-ground light offers an aesthetic light source for a wide range of architectural applications. This stainless steel unit is IP68 rated and utilises a toughened glass lens for added safety.

Manufactured complete with an integrated plug-and-play cable for easy installation.

FEATURES

- IP68
- Clean and neat outlooking design
- Uses CREE LED - low maintenance cost
- Class III electrical connections
- Dedicated thermal management guarantees LED lifetime @ 40,000 hours
- No UV or IR in the light beam
- Compatible with fixed output systems



Cut out ø50mm

Parameter	Specification	
Light Source	CREE LED	
Power Consumption (W)	1	
LED Current (mA)	DC 350	
Operating Voltage (V)	AC 100-240V 50/60Hz	
Colour Temperature (K)	3000	5000
Luminous Flux @ 12° (lm)	100	100
Luminous Flux @ 45° (lm)	100	100
CRI (Ra)	> 70 (4000K & 6000K)	
Lifetime (Hrs)	40,000	
Ingress Protection (IP)	68	
LED Working Temp. (°C)	<70	
Operating Temp. (°C)	-20 to +40	
Driver Options	Driver sold separately	