

3W	Colour Temp (K)	Red	Green	Blue
	Luminous Flux @ 45° (lm)	22	45	9

PRODUCT CODE

LT-Ingr-3 RGB/ / / /

LED COLOUR
RGB RGB Colour Change
BEAM ANGLE
 45 45°
FINISH
ST Stainless Steel

APPLICATIONS

Designed for use in areas such as pathways, lobbies, decking, ponds, and swimming pools - the LT-Ingr-3 RGB luminaire is very versatile.


DESCRIPTION

The LT-Ingr-3 RGB in-ground light offers an aesthetic light source for a wide range of architectural applications. This stainless steel unit is IP68 rated and utilises a toughened glass lens for added safety.

Manufactured complete with an integrated plug-and-play cable for easy installation.

FEATURES

- IP68
- Clean and neat outlooking design
- Uses RGB Tri-Chip LED - low maintenance cost
- Class III electrical connections
- Dedicated thermal management guarantees LED lifetime @ 50,000 hours
- No UV or IR in the light beam
- Compatible with fixed output systems



Cut out ø50mm

Parameter	Specification		
Light Source	CREE LED		
Power Consumption (W)	3		
LED Current (mA)	DC 350		
Operating Voltage (V)	AC 100-240V 50/60Hz		
Colour Temperature (K)	Red	Green	Blue
Luminous Flux @ 45° (lm)	22	45	9
CRI (Ra)	> 70		
Lifetime (Hrs)	40,000		
Ingress Protection (IP)	68		
LED Working Temp. (°C)	<70		
Operating Temp. (°C)	-20 to +40		
Driver Options	Driver sold separately		